

BONNEVILLE PERFORMANCE

INSTRUCTIONS FOR INSTALLATION OF BONNEVILLE PERFORMANCE INSTRUMENT CUPS

1. PLACE YOUR MOTORCYCLE ON THE CENTER STAND OR SIDE STAND AND INSURE THAT IT IS STABLE.
2. PLACE A SOFT CLOTH OVER YOUR FRONT FENDER SO THAT IT IS PROTECTED FROM ANY TOOLS YOU MAY DROP.
3. REMOVE YOUR SPEEDO CABLE AND PULL IT DOWN AWAY FROM THE INSTRUMENT CUPS.
4. REMOVE THE TWO SIDE BOLTS FROM THE FORK EARS THAT SECURE YOUR HEADLAMP.
5. ALLOW YOUR HEADLANP TO DROP TO THE POINT THAT IT IS AWAY FROM THE INSTRUMENTS AND THERE IS SUFFICIENT ROOM TO REMOVE THE STOCK CUPS.
6. REMOVE THE TWO ACORN NUTS FROM EACH OF THE STOCK CUPS AND SLIP OFF THE PLASTIC CUPS FROM THE INSTRUMENTS. BE CAREFUL NOT TO PULL ON THE INSTRUMENT WIRES.
7. RETAIN THE FLAT WASHER AND ACORN NUTS.
8. ALIGN THE BONNEVILLE PERFORMANCE INSTRUMENT CUPS WITH THE MACHINED SLOTS FOR THE INSTRUMENT WIRES AND SLIP ON.
9. ADD THE ENCLOSED LOCK WASHER TO THE ACORN NUT AND FLAT WASHER AND FASTEN INTO PLACE JUST LIKE THE STOCK CUPS.
10. REPLACE YOUR SPEEDO CABLE AND CAREFULLY HAND-TIGHTEN TO AVOID CROSS-THREADING.
11. REPLACE YOUR HEADLAMP AND SECURE THE FASTENERS.

MAINTENANCE OF YOUR BONNEVILLE PERFORMANCE INSTRUMENT CUPS

USE ANY ALUMINUM/ALLOY POLISH SUCH AS MOTHERS, WENOL OR SEMICHROME TO MAINTAIN THE LUSTER.